ATTACHMENT A

THIS IS A DRAFT COPY <u>ONLY</u> AND IS NOT AN OFFICIAL COPY OF THE FINAL, ADOPTED ORDINANCE

ORDINANCE G-

AN ORDINANCE AMENDING THE ZONING DISTRICT MAP ADOPTED PURSUANT TO SECTION 601 OF THE CITY OF PHOENIX ZONING ORDINANCE BY CHANGING THE ZONING DISTRICT CLASSIFICATION FOR THE PARCEL DESCRIBED HEREIN (CASE Z-58-25-6) FROM R1-6 (SINGLE-FAMILY RESIDENCE DISTRICT) TO R-O (RESIDENTIAL OFFICE – RESTRICTED COMMERCIAL DISTRICT).

BE IT ORDAINED BY THE COUNCIL OF THE CITY OF PHOENIX, as follows:

SECTION 1. The zoning of a 1.12-acre site located at the southeast corner of 17th Street and Griswold Road in a portion of Section 34, Township 3 North, Range 3 East, as described more specifically in Exhibit "A," is hereby changed from "R1-6" (Single-Family Residence District) to "R-O" (Residential Office – Restricted Commercial District).

SECTION 2. The Planning and Development Director is instructed to modify the Zoning Map of the City of Phoenix to reflect this use district classification change as shown in Exhibit "B."

SECTION 3. Due to the site's specific physical conditions and the use district applied for by the applicant, this rezoning is subject to the following stipulations, violation of which shall be treated in the same manner as a violation of the City of Phoenix Zoning Ordinance:

- 1. All building elevations shall contain architectural embellishments and detailing such as textural changes, pilasters, offsets, recesses, variation in window size and location, and/or overhang canopies, as approved by the Planning and Development Department.
- 2. A minimum 20-foot-wide landscape setback shall be provided along the property line adjacent to Griswold Road.
- 3. A minimum 10-foot-wide landscape setback shall be provided along the property line adjacent to 17th Street.
- 4. A minimum 10-foot-wide landscape setback shall be provided along the east property line.
- 5. Landscape setbacks shall be planted to the following standards, as approved by the Planning and Development Department.
 - a. Minimum 2-inch caliper, large canopy, drought-tolerant, shade trees, planted 30 feet on center, or in equivalent groupings.
 - b. A minimum of five, 5-gallon drought-tolerant shrubs per tree.
 - c. A mixture of drought-tolerant shrubs, accents, and vegetative groundcovers, evenly distributed throughout the landscape areas to achieve a minimum of 50% live coverage.
- 6. Where pedestrian walkways cross a vehicular path, the pathway shall be constructed of decorative pavers, stamped or colored concrete, or other pavement treatments that visually contrast parking and drive aisle surfaces, as approved by the Planning and Development Department.
- 7. No vehicular access, except for fire access, may be permitted along Griswold Road. All fire access shall be mountable curb with reinforced concrete per MAG detail, as approved by the Planning and Development Department.
- 8. Right-of-way shall be dedicated at the southeast corner of 17th Street and Griswold Road to encompass all public infrastructure, as approved by the Planning and Development Department.

- 9. Should the applicant be successful in obtaining a variance to allow access from other than a collector or arterial street, a shared driveway and access easement shall be identified on the plat along 17th Street, between the subject site and the property to the south (APN No. 165-21-006A).
- 10. All streets within and adjacent to the development shall be constructed with paving, curb, gutter, sidewalk, curb ramps, streetlights, median islands, landscaping and other incidentals, as per plans approved by the Planning and Development Department. All improvements shall comply with all ADA accessibility standards.
- 11. A minimum of 5% of the required parking spaces shall include EV Installed infrastructure.
- 12. A minimum of four bicycle parking spaces shall be provided through Inverted U and/or artistic racks located near building entrances and installed per the requirements of Section 1307.H. of the Phoenix Zoning Ordinance, as approved by the Planning and Development Department. Artistic racks shall adhere to the City of Phoenix Preferred Designs in Appendix K of the Comprehensive Bicycle Master Plan.
- 13. All bicycle parking spaces and pedestrian pathways, including sidewalks, shall be shaded by a structure, landscaping, or a combination of the two to provide a minimum of 75% shade, as approved by the Planning and Development Department.
- 14. Natural turf shall only be utilized for required retention areas (bottom of basin, and only allowed on slopes if required for slope stabilization), as approved by the Planning and Development Department.
- 15. A minimum of 25% of the surface parking areas shall be shaded, as approved by the Planning and Development Department. Shade may be achieved by structures or by minimum 2-inch caliper, drought tolerant, shade trees, or a combination thereof.
- 16. Prior to final site plan approval, documentation shall be provided that demonstrates a commitment to participate in the Phoenix Water Efficiency Checkup program for a minimum of 10 years, or as approved by the Planning and Development Department
- 17. A minimum of two green stormwater infrastructure (GSI) elements for stormwater management shall be implemented, as approved or modified by the Planning and Development and/or Street Transportation departments. This includes but is not limited to stormwater harvesting basins, bioswales,

- permeable pavement, etc., per the Greater Phoenix Metro Green Infrastructure and Low Impact Development Details for Alternative Stormwater Management.
- 18. If determined necessary by the Phoenix Archaeology Office, the applicant shall conduct Phase I data testing and submit an archaeological survey report of the development area for review and approval by the City Archaeologist prior to clearing and grubbing, landscape salvage, and/or grading approval.
- 19. If Phase I data testing is required, and if, upon review of the results from the Phase I data testing, the City Archaeologist, in consultation with a qualified archaeologist, determines such data recovery excavations are necessary, the applicant shall conduct Phase II archaeological data recovery excavations.
- 20. In the event archaeological materials are encountered during construction, the developer shall immediately cease all ground-disturbing activities within a 33-foot radius of the discovery, notify the City Archaeologist, and allow time for the Archaeology Office to properly assess the materials.
- 21. Prior to final site plan approval, the landowner shall execute a Proposition 207 waiver of claims form. The waiver shall be recorded with the Maricopa County Recorder's Office and delivered to the City to be included in the rezoning application file for record.
- 22. All vegetation planted in association with this site, including the streetscape, shall consist entirely of plant species indigenous to the Upper Sonoran Desert, as approved by the Planning and Development Department.
- 23. All sidewalks adjacent to the streets shall be detached with a minimum 5-foot-wide continuous landscape area located between the back of curb and sidewalk. The landscape area shall be planted to the following standards, as approved by the Planning and Development Department.
 - a. Minimum 2-inch caliper, single-trunk, large canopy, shade trees, planted 20 feet on center, or in equivalent groupings.
 - b. A mixture of shrubs, accents, and vegetative groundcovers, maintained to a maximum height of 24 inches to provide a minimum of 75% live coverage.
- 24. The following lighting standards shall apply on-site, as approved by the Planning and Development Department.
 - a. All lighting shall be shielded to prevent direct visibility of the light source from adjacent property.

- b. Lighting shall be shielded with cut-off fixtures and deflectors to direct light downward and limit on-site lighting levels to a maximum of 1 foot candle at the property line.
- c. Any lighting shall not exceed a maximum of 15 feet in height including lamp, pole, and base.
- d. The color temperature of any lighting shall be limited to 2,700 kelvins.
- 25. A sign shall be installed at any driveway along 17th Street to discourage right turn egress on 17th Street.

SECTION 4. If any section, subsection, sentence, clause, phrase or portion of this ordinance is for any reason held to be invalid or unconstitutional by the decision of any court of competent jurisdiction, such decision shall not affect the validity of the remaining portions hereof.

PASSED by the Council of the City of Phoenix this 3rd day of September, 2025.

	MAYOR
ATTEST:	
Denise Archibald, City Clerk	
APPROVED AS TO FORM: Julie M. Kriegh, City Attorney	
By:	

REVIEWED BY:

Jeffrey Barton, City Manager

Exhibits:

A – Legal Description (1 Page)
B – Ordinance Location Map (1 Page)

EXHIBIT A

LEGAL DESCRIPTION FOR Z-58-25-6

A PORTION OF THE SOUTHWEST QUARTER OF SECTION 34, TOWNSHIP 3 NORTH, RANGE 3 EAST OF THE GILA AND SALT RIVER BASE AND MERIDIAN, MARICOPA COUNTY, ARIZONA DESCRIBED AS FOLLOWS:

BEGINNING AT THE SOUTHWEST CORNER OF SECTION 34, TOWNSHIP 3 NORTH, RANGE 3 EAST;

THENCE SOUTH 89 DEGREES 36 MINUTES 15 SECONDS EAST, A DISTANCE OF 649.16 FEET;

THENCE NORTH 00 DEGREES 02 MINUTES 15 SECONDS WEST, A DISTANCE OF 653.59 FEET TO A FOUND BRASS CAP AT THE INTERSECTION OF NORTHERN AVENUE AND 17TH STREET;

THENCE CONTINUING NORTH 00 DEGREES 02 MINUTES 15 SECONDS WEST, A DISTANCE OF 270.37 FEET ALONG THE CENTER LINE OF 17TH STREET;

THENCE NORTH 89 DEGREES 53 MINUTES 09 SECONDS EAST, A DISTANCE OF 25.00 FEET TO A POINT ON THE EAST RIGHT OF WAY LINE OF SAID 17TH STREET, SAID POINT BEING THE TRUE POINT OF BEGINNING;

THENCE NORTH 00 DEGREES 02 MINUTES 15 SECONDS WEST, A DISTANCE OF 215.41 FEET TO A TANGENT CONCAVE CURVE TO THE RIGHT:

THENCE ALONG SAID CURVE TO THE RIGHT, HAVING A RADIUS OF 25.48 FEET, AND A DEL TA OF 76°16'04", 33. 91 FEET;

THENCE NORTH 76 DEGREES 13 MINUTES 49 SECONDS EAST A DISTANCE OF 131.65 FEET;

THENCE SOUTH 00 DEGREES 02 MINUTES 41 SECONDS EAST A DISTANCE OF 271.31 FEET:

THENCE SOUTH 88 DEGREES 49 MINUTES 58 SECOND WEST A DISTANCE OF 5.01 FEET;

THENCE SOUTH 89 DEGREES 57 MINUTES 45 SECONDS WEST A DISTANCE OF 142.35 FEET TO THE TRUE POINT OF BEGINNING.

